

KIC KRONES high-tech adhesives

KRONES colfix S 4018 synthetic/casein label adhesive

Properties

- High initial adhesion
- Excellent runnability
- Easy cleaning of machine parts

Application

- Labelling and foil spraying of warm, cold, dry and wet glass containers
- Suitable for all machine outputs
- Good leach solubility in the cleaning machine
- Very low consumption figures
- Excellent experience in the wine and spirits industry

Technical data

Adhesive type:	Based on synthetic and natural polymers
pH:	approx. 8
Viscosity (Brookfield 7/20, 20 °C):	approx. 80,000 – 130,000 mPa·s (cps)
Processing temperature:	approx. 26 – 32 °C
Solids content:	approx. 39 %
Density:	approx. 1.1
Cold resistance:	Sensitive to frost; adhesive is no longer usable once frozen
Shelf life:	6 months if stored appropriately
Dilution:	The adhesive is supplied ready to use and must not be diluted.
Cleaning:	warm water



The above mentioned information is based on knowledge and experience acquired in the field. However, due to the variety of materials and operating conditions beyond our control, we recommend that you definitely conduct your own extensive tests. Therefore information contained in this publication or provided in a consultation in no way implies legal liability.

KIC KRONES
Böhmerwaldstraße 5
93073 Neutraubling
Germany

Phone: +49 9401 70-0
Fax: +49 9401 70-3696
E-mail: kic@krones.com
Internet: www.kic-krones.com

 **KIC KRONES**
KRONES GROUP